

## ANSI 150 & 300

Directive 97/23/CE N° 0036 - H 1 module - Risk category III - A 216 WCB cast steel body / TRIM 8.1/2 Stellite - ANSI B16.10 - RF flanges - Max. pressure 20 bar (ANSI 150), 50 bar (ANSI 300) - Temperature -29°C to +425°C.

### Gate valves



143 - Flanged ANSI 150 RF

Ø	50	65	80	100	150	200	250	300
face to face	177,8	190,5	203,2	228,6	266,7	292,1	330,2	355,6
code	143050	143065	143080	143100	143150	143200	143250	143300



144 - Flanged ANSI 300 RF

Ø	50	65	80	100	150	200	250	300
face to face	215,9	241,3	282,4	304,8	403,4	419,1	475,2	501,7
code	144050	144065	144080	144100	144150	144200	144250	144300

### Globe valves



443 - Flanged ANSI 150 RF

Ø	50	65	80	100	150	200	250
code	443050	443065	443080	443100	443150	443200	443250

### Swing type check valves



373 - Flanged ANSI 150 RF  
410 swing - SLT6 seat.

Ø	50	65	80	100	150	200	250	300
face to face	203,2	216,1	241,3	292,1	355,6	495,3	622,3	698,5
code	373050	373065	373080	373100	373150	373200	373250	373300

### Y-strainers



243 - Flanged ANSI 150 RF  
Stainless steel 316 filter - Mesh 15/10°.

Ø	50	80	100	150	200	250	300
face to face	203	241	292	406	445	622	699
code	243050	243080	243100	243150	243200	243250	243300