

Back pressure valves



2480 - Stainless steel back pressure valve

Stainless steel body - FPM seat - PN 16 - Temperature range: -15°C/+100°C - BSP threaded - Supplied with a stainless steel pressure gauge indicating the upstream pressure.



DN	Face to face (mm)	Weight (kg)	upstream pressure range	
			1-5 bar code	4-10 bar code
1/2"	70	0,80	248001	248002
3/4"	85	1,00	248011	248012
1"	92	1,05	248021	248022
1 1/2"	115	2,30	248031	248032
2"	120	2,50	248041	248042
50	190	12	-	249042
65	210	16	-	249052
80	225	18	-	249062
100	250	25	-	249072

Pressure reducing valves

2440 - Stainless steel pressure reducing valve

SS 316 body - FPM seat - PN 16 - Temperature range: -15°C/+100°C - BSP or flanged connections - Supplied with a stainless steel pressure gauge indicating the downstream pressure.



DN	Face to face (mm)	Weight (kg)	downstream pressure range		
			1-6 bar code	4-10 bar code	8-13 bar code
1/2"	70	0,80	244001	244002	244003
3/4"	85	1,00	244011	244012	244013
1"	92	1,05	244021	244022	244023
1 1/2"	115	2,30	244031	244032	244033
2"	120	2,50	244041	244042	244043

Flanged PN 16

downstream pressure range

DN	Face to face (mm)	Weight (kg)	1-6 bar	4-10 bar
			code	code
15	150	2	245001	-
20	150	3	245011	-
25	150	5	245021	-
40	190	8	245031	-
50	190	12	245041	245042
65	210	16	245051	245052
80	225	18	245061	245062
100	250	25	245071	245072

